



Over 100 Years of Experience

304 Stainless Steel Self-Tapping Fasteners

Indented hex head

.0003 minimum cadmium plated

Available with or without 15mm O.D. Neo Bond stainless steel washers

	Size	Point	Carton Qty.
	#14 x 3/4"	A-AB-B	2,500
	#14 x 1"	A-AB-B	2,500
	#14 x 1-1/4"	A	2,000
	#14 x 1-1/2"	A-AB-B	1,500
	#14 x 2"	A-B	1,000
	#14 x 2-1/2"	A-AB-B	1,000
	#14 x 3"	A-B	1,000
	#14 x 3-1/2"	B	500
	#14 x 4"	A-B	500
	#14 x 5"	A-B	300
	#14 x 6"	A-B	250
	#17 x 3/4"	AB	2,500
	#17 x 1"	AB	2,000
	#17 x 1-1/2"	AB	1,500

304 STAINLESS STEEL

FASTENER STRENGTH

(Tensile Values Are For Hex Washer Head & Hex Head Fasteners)

Fastener Diameter	Minimum Tensile (lbs.)	Minimum Torque (In lbs.)	Minimum Shear (lbs.)
#14-10	2,925	125	1,925
1/4-14	3,600	150	2,600
#17-14	5,200	170	3,125



www.atlasfasteners.com

1628 Troy Road • Ashland Ohio, 44805
T: 419-289-6171 • F: 419-289-2564

800-321-6977

SALES AND SERVICE CENTERS

Ashland, Ohio
1-800-321-6977


Flat Rock, NC
1-800-364-0370

Houston, TX
1-800-503-2105

Salem, OR
1-800-547-8740



Over 100 Years of Experience



PULL-OVER VALUES (lbs.) 15mm BONDED EPDM WASHER

Gauge					
Size	18 (.050)	20 (.040)	22 (.0299)	24 (.0239)	26 (.0179)
#14-10	2,350	1,750	1,325	950	650
1/4-14	2,350	1,750	1,325	950	650
#17-14	2,250	1,650	1,225	850	550

SUGGESTED DRILL SIZE/PULL-OUT VALUES
(#14 and 1/4" diameters)

Steel Thickness	Point Type	Drill Size	Average Ultimate Pull-out
26 Gauge (.018)	A-AB	1/8" (.125)	243 lbs.
24 Gauge (.024)	A-AB	1/8" (.125)	340 lbs.
22 Gauge (.030)	A-AB	5/32" (.156)	372 lbs.
20 Gauge (.036)	A-AB	5/32" (.156)	412 lbs.
18 Gauge (.048)	A-AB-BP	3/16" (.187)	518 lbs.
16 Gauge (.060)	A-AB-B-BP	3/16" (.187)	850 lbs.
14 Gauge (.075)	AB-B-BP	#7 (.201)	1,318 lbs.
12 Gauge (.105)	AB-B-BP	#7 (.201)	1,681 lbs.
1/8" (.125)	AB-B-BP	#2 (.221)	1,780 lbs.
10 Gauge (.134)	AB-B-BP	#2 (.221)	1,812 lbs.
3/16" (.187)	B-BP	#2 (.221)	2,855 lbs.
1/4" (.250)	B-BP	#2 (.221)	3,355 lbs.
3/8" (.375)	B-BP	#2 (.221)	*3,391 lbs.
1/2" (.500)	B-BP	#1 (.228)	*3,500 lbs.



www.atlasfasteners.com

1628 Troy Road • Ashland Ohio, 44805
T: 419-289-6171 • F: 419-289-2564

800-321-6977

SALES AND SERVICE CENTERS

Ashland, Ohio
1-800-321-6977

Flat Rock, NC
1-800-364-0370

Houston, TX
1-800-503-2105

Salem, OR
1-800-547-8740