



Over 100 Years of Experience

EnduraFast ACQ Lumber Fastener

Won't Rust in ACQ Treated Wood

Easy Installation

High hex head design provides for positive socket fit and stability during installation

Magnetic 410 stainless stays in the socket

Coarse thread pitch provides fast penetration

Painted Head

Stocked in standard panel colors

Sizes

Available in lengths of 1", 1-1/2" and 2"

Convenience

Conveniently bagged at 100 pieces per
Clearly marked for use in treated lumber
Black Coating

Makes the ACQ fastener easy to identify

Provides additional corrosion resistance



Diameter: #10

Threads per In.: 14

Length: 1", 1 1/2", 2"

Point: Sharp


Material: 410 Stainless Steel

Coating: Mech. Zinc w/Black Coating

Engineering Test Report

Fastener Diameter	Minimum Torsional	Minimum Tensile	Minimum Shear
#10	68 in. lbs.	1817 lbs.	1216 lbs.

Pull Out Values



TEST MATERIAL	PENETRATION	RESULTS
S-P-F #2	1"	498
S-P-F #2	1-1/2"	899
Hem Fir #2	1"	694
Hem Fir #2	1-1/2"	1080
1/2 CDX	FULL	361
5/8 CDX	FULL	490
3/4 CDX	FULL	560

Note: Pull-out values are a measurement of wood material strength. Actual field values may vary.



www.atlasfasteners.com

1628 Troy Road • Ashland Ohio, 44805

T: 419-289-6171 • F: 419-289-2564

800-321-6977

SALES AND SERVICE CENTERS

Ashland, Ohio
1-800-321-6977

Flat Rock, NC
1-800-364-0370

Houston, TX
1-800-503-2105

Salem, OR
1-800-547-8740