

ATLAS

BUILDING PRODUCTS

A MARMON BERKSHIRE HATHAWAY COMPANY

PRODUCT SPECIFICATION SHEET

#10 WOODTITE HLX[®] HI-LOW



**ASHLAND
OHIO**

1628 TROY ROAD
ASHLAND, OH 44805
(800) 321-6977

**FLAT ROCK
NORTH CAROLINA**

161 COMMERCIAL BLVD
FLAT ROCK, NC 28731
(828) 692-2603

**HOUSTON
TEXAS**

4822 N. SAM HOUSTON PKWY W.
SUITE 100
HOUSTON, TX 77086
(800) 503-2105

#10 WOODTITE HLX[®] HI-LOW



Head

1/4" hex head

Thread

Threads per inch: 14, Hi-Low design

Point

Type-17 26 degree sharp point to penetrate metal quickly while minimizing chips

Washer

Bonded seal washer

Material

Carbon steel

Finish

Mechanically plated with long life coating

SIZE	ITEM #	BOX QTY
10-14 x 1	82639ZBN99XXHSL	3,000
10-14 x 1-1/2	82642ZBN99XXHSL	2,500
10-14 x 2	82644ZBN99XXHSL	2,000
10-14 x 2-1/2	82646ZBN99XXHSL	1,000
10-14 x 3	82648ZBN99XXHSL	1,000

STRENGTH CHARACTERISTICS

MINIMUM TORSIONAL	MINIMUM TENSILE	MINIMUM SHEAR
68 in.-lbs.	2,100 lbs.	1,265 lbs.

PULL OUT VALUES

MATERIALS	PULL OUT VALUES
7/16" OSB	268 lbs.
5/8" OSB	276 lbs.
SPF2 w/1.5in. penetration	1,090 lbs.

All test results and recommendations are based on laboratory tests. Specific job site conditions should be taken into consideration when specifying the proper fastener. Actual field values may vary, therefore we assume no liability for use of this information. Pull out values are a measurement of wood material strength. Use of impact style guns for installation not recommended.