

METAL TO METAL FASTENERS

# #1/4-14 FLAT TOP® SELF DRILLING



**HEAD**

5/16" hex head

**THREAD**

Threads per inch: 14

**POINT**

TCP self drilling point

**WASHER**

EPDM tubular washer

**MATERIAL**


Carbon steel

**FINISH**

Mechanically plated with long life coating

**PRODUCT SUPERIORITY**

- ≡ Special Undercut entraps EPDM sealing washer, even at extreme angles
- ≡ One-Piece Design eliminates damage to washer surface
- ≡ Higher Hex provides positive socket engagement
- ≡ Flat-Top Design stabilizes socket during installation



**PULL-OUT VALUES**

STEEL THICKNESS	VALUES
22	296 lbs.
20	349 lbs.
18	613 lbs.
16	883 lbs.
14	1148 lbs.
12	1861 LBS.
1/8"	2409 LBS.
3/16"	4553 LBS.

**STRENGTH CHARACTERISTICS**

MINIMUM TENSILE	MINIMUM TORSIONAL	MINIMUM SHEAR
3850 lbs.	150 in.- lbs.	2600 lbs.

All test results and recommendations are based on laboratory tests. Specific job site conditions should be taken into consideration when specifying the proper fastener. Actual field values may vary, therefore we assume no liability for use of this information. Pull out values are a measurement of wood material strength.



Scan here for more product information and to view our entire catalog!

**ASHLAND, OH**


1628 TROY RD  
ASHLAND, OH 44805  
(800) 321-6977

**FLAT ROCK, NC**

161 COMMERCIAL BLVD  
FLAT ROCK, NC 28731  
(828) 692-2603

**HOUSTON, TX**

4822 N. SAM HOUSTON PKWY W., STE 100  
HOUSTON, TX 77086  
(800) 503-2105



### SHEAR VALUES

For Carbon Steel Self-Drilling Fasteners

SIZE	POINT	2x26 (0.036)	2x24 (0.046)	2x22 (0.060)	2x20 (0.072)	2x18 (0.096)	2x16 (0.120)	2x14 (0.150)	2x12 (0.210)	2x1/8 (0.250)	2x3/16 (0.375)	2x1/4 (0.500)
12-14	TCP1	435	706	756	1021	1455	/	/	/	/	/	/
1/4-14	TCP1	514	852	888	1247	1767	/	/	/	/	/	/
8-18	TCP2	297	499	563	743	1063	1081	/	/	/	/	/
10-16	TCP2	315	481	592	833	1209	1271	/	/	/	/	/
12-14	TCP2	368	603	626	901	1373	1761	2141	/	/	/	/
8-18	TCP3	/	/	/	733	1093	1213	1217	/	/	/	/
10-16	TCP3	/	/	/	731	1269	1543	1555	/	/	/	/
10-24	TCP3	/	/	/	754	1211	1557	1697	/	/	/	/
12-14	TCP3	/	/	/	772	1361	1623	1973	1989	/	/	/
1/4-14	TCP3	/	/	/	933	1445	2103	2587	2653	2823	/	/
12-24	TCP4	/	/	/	/	/	/	/	2051	2703	/	/
12-24	TCP5	/	/	/	/	/	/	/	/	2703	2723	2765

### DRILL POINT CAPABILITIES

#### Material Thickness

