

METAL TO WOOD FASTENERS

#10 ENDURAFAST 410 STAINLESS



HEAD

5/16" hex head

THREAD

14

DIAMETER

#10

POINT

26 Degree sharp point for quick piercing

LENGTH

1", 1-1/2", 2"

WASHER

Bonded Sealing Washer

MATERIAL

410 Stainless Steel

FINISH

Black coating makes the ACQ fastener easier to identify

Provides additional corrosion resistance for internal and external applications

PRODUCT SUPERIORITY

- ≡ New Design allows for faster installation
- ≡ Won't rust in ACQ treated wood
- ≡ Patented Anti-Backout design
- ≡ 26° Sharp point pierces steel panels faster than traditional metal-to-wood fasteners
- ≡ Can be painted industry standard colors

PULL OUT VALUES

Test Material	Penetration	Result
S-P-F #2	1"	498
S-P-F #2	1-1/2"	899
Hem Flr #2	1"	694
Hem Flr #2	1-1/2"	1,080
1/2 CDX	Full	361
5/8 CDX	Full	490
3/4 CDX	Full	560

STRENGTH CHARACTERISTICS

MINIMUM TORSIONAL	MINIMUM TENSILE	MINIMUM SHEAR
68 in. lbs.	1,817 lbs.	1,216 lbs.

All test results and recommendations are based on laboratory tests. Specific job site conditions should be taken into consideration when specifying the proper fastener. Actual field values may vary, therefore we assume no liability for use of this information. Pull out values are a measurement of wood material strength.

Installation Instructions - Do not use impact style guns. Use an electric screw gun with 2,500 RPM max.



Scan here for more product information and to view our entire catalog!

ASHLAND, OH

1628 TROY RD
ASHLAND, OH 44805
(800) 321-6977

FLAT ROCK, NC

161 COMMERCIAL BLVD
FLAT ROCK, NC 28731
(828) 692-2603

HOUSTON, TX

4822 N. SAM HOUSTON PKWY W., STE 100
HOUSTON, TX 77086
(800) 503-2105